

EXTRACCIÓN DUCT **IN-LINE**



# MT-125

Cod. **00720000** EAN **8422248920520**




## INFORMACIÓN GENERAL

| | |
|---|---|
| EAN/UPC | 8422248920520 |
| Subfamily | In Line |

## General features

| | |
|---|---|
| Motor type | AC/SHADED POLE |
| Motor Model | SP5820 |
| Motor power (W) | 20 |
| Lightning Technology | N/A |
| Light Quantity | N/A |
| Filter Type | N/A |
| Number of layers | N/A |
| Control description | N/A |
| Power levels | N/A |
| Timer | - |
| Timer Hygro | - |
| Electronic filter saturation indicator | - |
| Dimmable lighting | - |

## Installation

| | |
|---|---|
| Width (mm) | 118 |
| Height (mm) | 118 |
| Depth (mm) | 96 |
| Total minimum height (mm) | 2300 |
| Outlet diameter (mm) | 118 |
| Maximum pressure (Pa) | 48 |
| Anti-return flap included | - |
| Easy installation system | No |

## Power connection

| | |
|---|---|
| Rated voltage (V) | 220-240 |
| Rated frequency (Hz) | 50/60 |
| Rated power input (W) | 20 |
| Protection against electric shock | Class II |
| Plug type | No plug |

## Accessories

| | |
|---|---|
| Fixed Grid | 1920200 |
| Overpressure shutter | 1920300 |
| Support | 1991000 |

## Power and water connection

| | |
|---|---|
| Rated voltage (V) | 220-240 |
| Rated frequency (Hz) | 50/60 |
| Rated power input (W) | 20 |
| Protection against electric shock | Class II |
| Plug type | No plug |