



### INFORMACIÓN GENERAL

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248003438 |
| Subfamily | Axial         |

### General features

|                                        |                |
|----------------------------------------|----------------|
| Motor type                             | AC/SHADED POLE |
| Motor Model                            | SP5820         |
| Motor power (W)                        | 20             |
| Lightning Technology                   | N/A            |
| Light Quantity                         | N/A            |
| Filter Type                            | N/A            |
| Number of layers                       | N/A            |
| Control description                    | N/A            |
| Power levels                           | 1              |
| Timer                                  | √              |
| Timer Hygro                            | -              |
| Electronic filter saturation indicator | -              |
| Dimmable lighting                      | -              |

### Installation

|                           |           |
|---------------------------|-----------|
| Width (mm)                | 170       |
| Height (mm)               | 170       |
| Depth (mm)                | 1355      |
| Total minimum height (mm) | 170       |
| Outlet diameter (mm)      | 118       |
| Anti-return flap included | √         |
| Easy installation system  | Quick-Fix |

### Power connection

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 230      |
| Rated frequency (Hz)              | 50/60    |
| Rated power input (W)             | 20       |
| Protection against electric shock | Class II |
| Plug type                         | No plug  |

### Accessories

|                     |                                   |
|---------------------|-----------------------------------|
| Fixed Grid          | QUICK FIX GRIP                    |
| Backdraught Shutter | Backdraught shutters incorporated |


### Power and water connection

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 230      |
| Rated frequency (Hz)              | 50/60    |
| Rated power input (W)             | 20       |
| Protection against electric shock | Class II |
| Plug type                         | No plug  |

## X-MART 12 TIMER

Cod. 01021000

EAN 8422248003438



|           | Ø A | B   | C     | D  |
|-----------|-----|-----|-------|----|
| X-MART 10 | 98  | 150 | 89,5  | 31 |
| X-MART 12 | 118 | 170 | 103,5 | 32 |
| X-MART 15 | 148 | 194 | 123,5 | 35 |