




## X-MART 15 TIMER

Cod. 01031000

EAN 8422248003452



|           | Ø A | B   | C     | D  |
|-----------|-----|-----|-------|----|
| X-MART 10 | 98  | 150 | 89,5  | 31 |
| X-MART 12 | 118 | 170 | 103,5 | 32 |
| X-MART 15 | 148 | 194 | 123,5 | 35 |

### INFORMACIÓN GENERAL

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248003452 |
| Subfamily | Axial         |

### General features

|                                        |        |
|----------------------------------------|--------|
| Motor Model                            | SP5820 |
| Motor power (W)                        | 28     |
| Lighting Technology                    | LED    |
| Light Quantity                         | 1      |
| Filter Type                            | N/A    |
| Number of layers                       | N/A    |
| Control description                    | N/A    |
| Power levels                           | 1      |
| Timer                                  | √      |
| Timer Hygro                            | -      |
| Electronic filter saturation indicator | -      |
| Dimmable lighting                      | -      |

### Installation

|                           |           |
|---------------------------|-----------|
| Width (mm)                | 170       |
| Height (mm)               | 170       |
| Depth (mm)                | 1035      |
| Total minimum height (mm) | 118       |
| Outlet diameter (mm)      | 120       |
| Anti-return flap included | √         |
| Easy installation system  | Quick-Fix |

### Power connection

|                                   |         |
|-----------------------------------|---------|
| Rated voltage (V)                 | 220-240 |
| Rated frequency (Hz)              | 50/60   |
| Rated power input (W)             | 20      |
| Protection against electric shock | Class I |
| Power cord length (m)             | 50      |

### Accessories

|                     |                                   |
|---------------------|-----------------------------------|
| Fixed Grid          | QUICK FIX GRIP                    |
| Backdraught Shutter | Backdraught shutters incorporated |

### Power and water connection

|                                   |         |
|-----------------------------------|---------|
| Rated voltage (V)                 | 220-240 |
| Rated frequency (Hz)              | 50/60   |
| Rated power input (W)             | 20      |
| Protection against electric shock | Class I |
| Power cord length (m)             | 50      |