




OMEGA 900 X

Cod. 02004310

EAN 8422248190596



GENERAL INFORMATION

EAN/UPC	8422248190596
Subfamily	Chimney

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	105,4
EEl class (energy efficiency class)	C
FDE (fluid dynamic efficiency)	20
FDE class (fluid dynamic efficiency class)	C
LE (light efficiency) (lux/W)	21
LE class (light efficiency class)	B
GFE (grease filtering efficiency)	90,3
GFE class (grease filtering efficiency class)	B
Airflow in normal mode MIN (m3/h)	385
Airflow in normal mode MAX (m3/h)	645
Acoustic power in normal mode MIN (dB)	57,8
Acoustic power in normal mode MAX (dB)	71,8
Po (energy consumption in off mode) (W)	0
Ps (energy consumption in standby mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	1,3
EEl (Energy Efficiency Index)	77,6
QBEP (maximum efficiency at air flow point) (m3/h)	458,1
PBEP (maximum efficiency at pressure point) (Pa)	333,8
WBEP (power consumption at maximum efficiency) (W)	213
WL (nominal power lighting system) (W)	6
EMIDDLE (Average illuminance on the cooking surface) (lux)	126

External Dimensions

Width (mm)	900
Depth (mm)	500
Maximum total height (mm)	1020
Minimum total height (mm)	720
Diamètre de sortie (mm)	150, 125

Characteristics

Motor quantity	1
Motor model	TA
Maximum pressure (Pa)	430
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	-
Power levels	3
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	-
Remote control	-
Display	-

Lighting

Light model	CSLED
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	√
Charcoal filter	-

Back draught shutter	-
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	276
Electric shock protection	Class II
Power cord length (m)	0,7
Plug type	No plug

Accessories

Upper decorative duct extension	02862301
White decorative duct	No
Black decorative duct	No
Island tube booster	No
Back draught shutter	02832001
MAX PRO Metal filter	02800917
Activated charcoal filter	02859391
Noiseless flexible duct	02893002
Recirculation kit	02894000