



VK 6000 BK

Cod. 02061405

EAN 8422248357074



GENERAL INFORMATION

EAN/UPC	8422248357074
Subfamily	Chimney

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	24,8
EEl class (energy efficiency class)	A
FDE (fluid dynamic efficiency)	28,5
FDE class (fluid dynamic efficiency class)	B
LE (light efficiency) (lux/W)	31,6
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	71,4
GFE class (grease filtering efficiency class)	D
Airflow in normal mode MIN (m3/h)	166
Airflow in normal mode MAX (m3/h)	395
Acoustic power in normal mode MIN (dB)	49
Acoustic power in normal mode MAX (dB)	67
Po (energy consumption in off mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	1
EEl (Energy Efficiency Index)	48,5
QBEP (maximum efficiency at air flow point) (m3/h)	255,1
PBEP (maximum efficiency at pressure point) (Pa)	249,1
WBEP (power consumption at maximum efficiency) (W)	62
WL (nominal power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

External Dimensions

Width (mm)	600
Depth (mm)	475
Maximum total height (mm)	910
Minimum total height (mm)	670
Diamètre de sortie (mm)	150

Characteristics

Motor quantity	1
Motor model	K10 390 A
Maximum pressure (Pa)	290,8
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	-
Power levels	3
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	No
Remote control	-
Display	-

Lighting

Light model	CSLED
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	-
Charcoal filter	-
Back draught shutter	No

Inner shield	-
--------------	---

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	100
Electric shock protection	Class II
Plug type	No plug

Accessories

Upper decorative duct extension	'02862302
Back draught shutter	'02832004
MAX PRO Metal filter	'02800917
Activated charcoal filter	'02859489
Noiseless flexible duct	'02893002