



CG5-T600 X

Cod. 02005299

EAN 8422248097413



GENERAL INFORMATION

EAN/UPC	8422248097413
Subfamily	Curved Glass

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	46
EEL class (energy efficiency class)	B
FDE (fluid dynamic efficiency)	204
FDE class (fluid dynamic efficiency class)	C
LE (light efficiency) (lux/W)	4933
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	7386
GFE class (grease filtering efficiency class)	D
Airflow in normal mode MIN (m3/h)	3045
Airflow in normal mode MAX (m3/h)	499
Acoustic power in normal mode MIN (dB)	435
Acoustic power in normal mode MAX (dB)	676
Po (energy consumption in off mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	127
EEL (Energy Efficiency Index)	667
QBEP (maximum efficiency at air flow point) (m3/h)	260
PBEP (maximum efficiency at pressure point) (Pa)	270
WBEP (power consumption at maximum efficiency) (W)	957
WL (nominal power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	148

External Dimensions

Width (mm)	600
Depth (mm)	470
Maximum total height (mm)	776
Minimum total height (mm)	426
Diamètre de sortie (mm)	150

Characteristics

Motor quantity	1
Motor model	TT500
Maximum pressure (Pa)	430
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	-
Power levels	3
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	No
Remote control	-
Display	-

Lighting

Light model	ECOLED
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	√
Charcoal filter	-
Back draught shutter	Included

Inner shield	-
--------------	---

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50/60
Nominal input power (W)	123
Electric shock protection	Class I
Plug type	Type F

Accessories

Activated charcoal filter	02859492
Noiseless flexible duct	02893002