




## OMEGA 600 BK

Cod. 02002410

EAN 8422248109833



### GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248109833 |
| Subfamily | Chimney       |

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|                                               |      |
|-----------------------------------------------|------|
| AEC (Annual energy consumption) (kWh/year)    | 95,4 |
| EEl class (energy efficiency class)           | C    |
| FDE (fluid dynamic efficiency)                | 17,8 |
| FDE class (fluid dynamic efficiency class)    | D    |
| LE (light efficiency) (lux/W)                 | 33,3 |
| LE class (light efficiency class)             | A    |
| GFE (grease filtering efficiency)             | 90,3 |
| GFE class (grease filtering efficiency class) | B    |
| Airflow in normal mode MIN (m3/h)             | 385  |
| Airflow in normal mode MAX (m3/h)             | 645  |
| Acoustic power in normal mode MIN (dB)        | 57,8 |
| Acoustic power in normal mode MAX (dB)        | 71,8 |
| Po (energy consumption in off mode) (W)       | 0    |
| Ps (energy consumption in standby mode) (W)   | 0    |

### Integration directive EU 66/2014

|                                                            |       |
|------------------------------------------------------------|-------|
| f (time increase factor)                                   | 1,4   |
| EEl (Energy Efficiency Index)                              | 81,3  |
| QBEP (maximum efficiency at air flow point) (m3/h)         | 371,8 |
| PBEP (maximum efficiency at pressure point) (Pa)           | 314   |
| WBEP (power consumption at maximum efficiency) (W)         | 182,5 |
| WL (nominal power lighting system) (W)                     | 3     |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 100   |

### External Dimensions

|                           |          |
|---------------------------|----------|
| Width (mm)                | 600      |
| Depth (mm)                | 500      |
| Maximum total height (mm) | 890      |
| Minimum total height (mm) | 600      |
| Diamètre de sortie (mm)   | 150, 125 |

### Characteristics

|                                       |                        |
|---------------------------------------|------------------------|
| Motor quantity                        | 1                      |
| Motor model                           | TA                     |
| Maximum pressure (Pa)                 | 430                    |
| Filter technology                     | Aluminium mesh         |
| Control technology                    | Mechanical push button |
| Booster                               | -                      |
| Power levels                          | 3                      |
| Timer                                 | -                      |
| Filter saturation indicator           | -                      |
| Charcoal filter replacement indicator | -                      |
| Dimmer function                       | -                      |
| Connectivity                          | -                      |
| Remote control                        | -                      |
| Display                               | -                      |

### Lighting

|                |       |
|----------------|-------|
| Light model    | CSLED |
| Ray technology | LED   |

### Installation

|                                         |     |
|-----------------------------------------|-----|
| Minimum distance to electric plate (mm) | 650 |
| Minimum distance to gas plate (mm)      | 650 |
| Recirculation option                    | √   |
| Charcoal filter                         | -   |

|                      |    |
|----------------------|----|
| Back draught shutter | No |
| Inner shield         | -  |

**Electric connection**

|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 220-240  |
| Nominal frequency (Hz)    | 50       |
| Nominal input power (W)   | 273      |
| Electric shock protection | Class II |
| Power cord length (m)     | 0,7      |
| Plug type                 | No plug  |

**Accessories**

|                           |          |
|---------------------------|----------|
| White decorative duct     | No       |
| Black decorative duct     | No       |
| Island tube booster       | No       |
| Back draught shutter      | 02832001 |
| Activated charcoal filter | 02859391 |
| Noiseless flexible duct   | 02893002 |
| Recirculation kit         | 02894000 |