




X-MART 10 MATIC INOX T

Cod. **01046000**

EAN **8422248003735**



| | Ø A | B | C | D |
|-----------------|-----|-----|-----|--------|
| X-MART 10 MATIC | 98 | 150 | 87 | 38 máx |
| X-MART 12 MATIC | 118 | 170 | 101 | 38 máx |
| X-MART 15 MATIC | 148 | 194 | 120 | 38 máx |

GENERAL INFORMATION

| | |
|-----------|---------------|
| EAN/UPC | 8422248003735 |
| Subfamily | Axial |

General features

| | |
|--|----------------|
| Motor type | AC/SHADED POLE |
| Motor model | SP5820 |
| Motor power (W) | 18 |
| Lighting technology | LED |
| Light quantity | 1 |
| Filter type | N/A |
| Number of layers | N/A |
| Control description | N/A |
| Power levels | 1 |
| Timer | √ |
| Hygro timer | - |
| Electronic filter saturation indicator | - |
| Dimmable lighting | - |
| Special features | N/A |

Installation

| | |
|---------------------------|-----------|
| Width (mm) | 150 |
| Height (mm) | 150 |
| Depth (mm) | 125 |
| Total minimum height (mm) | 150 |
| Outlet diameter (mm) | 98 |
| Anti-return flap included | √ |
| Easy installation system | Quick-Fix |

Power connection

| | |
|---------------------------|----------|
| Nominal voltage (V) | 230-240 |
| Nominal frequency (Hz) | 50/60 |
| Nominal input power (W) | 15 |
| Electric shock protection | Class II |
| Plug type | No plug |

Accessories

| | |
|------------------|---------------------------|
| Fixed grill | QUICK FIX GRIP, |
| Backdraught seal | Automatic shutter system. |

Power and water connection

| | |
|---------------------------|----------|
| Nominal voltage (V) | 230-240 |
| Nominal frequency (Hz) | 50/60 |
| Nominal input power (W) | 15 |
| Electric shock protection | Class II |
| Plug type | No plug |