




## LEGEND 9010 X

Cod. **02029306**EAN **8422248110037**

### GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248110037 |
| Subfamily | Box           |

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|                                               |       |
|-----------------------------------------------|-------|
| AEC (Annual energy consumption) (kWh/year)    | 24,5  |
| EEI class (energy efficiency class)           | A+    |
| FDE (fluid dynamic efficiency)                | 37    |
| FDE class (fluid dynamic efficiency class)    | A     |
| LE (light efficiency) (lux/W)                 | 17    |
| LE class (light efficiency class)             | C     |
| GFE (grease filtering efficiency)             | 76,8  |
| GFE class (grease filtering efficiency class) | C     |
| Airflow in normal mode MIN (m3/h)             | 278,6 |
| Airflow in normal mode MAX (m3/h)             | 550,9 |
| Airflow in boost mode MIN (m3/h)              | 760,9 |
| Acoustic power in normal mode MIN (dB)        | 52    |
| Acoustic power in normal mode MAX (dB)        | 64    |
| Acoustic power boost mode (dB)                | 70    |
| Po (energy consumption in off mode) (W)       | 0,44  |
| Ps (energy consumption in standby mode) (W)   | 0,44  |

### Integration directive EU 66/2014

|                                                            |       |
|------------------------------------------------------------|-------|
| f (time increase factor)                                   | 0,7   |
| EEI (Energy Efficiency Index)                              | 39,6  |
| QBEP (maximum efficiency at air flow point) (m3/h)         | 316,9 |
| PBEP (maximum efficiency at pressure point) (Pa)           | 330   |
| WBEP (power consumption at maximum efficiency) (W)         | 78,6  |
| WL (nominal power lighting system) (W)                     | 6     |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 103   |

### External Dimensions

|                           |          |
|---------------------------|----------|
| Width (mm)                | 700      |
| Depth (mm)                | 495      |
| Maximum total height (mm) | 990      |
| Minimum total height (mm) | 745      |
| Diamètre de sortie (mm)   | 150, 125 |

### Characteristics

|                                       |                       |
|---------------------------------------|-----------------------|
| Motor quantity                        | 1                     |
| Motor model                           | BT4DC                 |
| Filter technology                     | Aluminium mesh        |
| Control technology                    | Electronic Soft Touch |
| Booster                               | √                     |
| Power levels                          | 4                     |
| Filter saturation indicator           | √                     |
| Charcoal filter replacement indicator | √                     |
| Dimmer function                       | √                     |
| Connectivity                          | √                     |
| Remote control                        | -                     |
| Display                               | Display_grafico       |

### Lighting

|                |               |
|----------------|---------------|
| Light model    | SSLED BICOLOR |
| Ray technology | LED           |

### Installation

|                                         |     |
|-----------------------------------------|-----|
| Minimum distance to electric plate (mm) | 650 |
| Minimum distance to gas plate (mm)      | 650 |
| Recirculation option                    | -   |
| Charcoal filter                         | -   |

|                      |    |
|----------------------|----|
| Back draught shutter | No |
| Inner shield         | -  |

#### Electric connection

|                           |         |
|---------------------------|---------|
| Nominal voltage (V)       | 220-240 |
| Nominal frequency (Hz)    | 50      |
| Nominal input power (W)   | 141     |
| Electric shock protection | Class I |
| Power cord length (m)     | 0,7     |
| Plug type                 | No plug |

#### Accessories

|                                 |          |
|---------------------------------|----------|
| Upper decorative duct extension | 02861301 |
| White decorative duct           | -        |
| Black decorative duct           | -        |
| Island tube booster             | -        |
| Back draught shutter            | 02832004 |
| Activated charcoal filter       | 02859318 |
| Noiseless flexible duct         | 02893002 |