



## CG5-T600 X

Cod. 02005299

EAN 8422248097413



### GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248097413 |
| Subfamily | Curved Glass  |

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|                                               |      |
|-----------------------------------------------|------|
| AEC (Annual energy consumption) (kWh/year)    | 46   |
| EEl class (energy efficiency class)           | B    |
| FDE (fluid dynamic efficiency)                | 204  |
| FDE class (fluid dynamic efficiency class)    | C    |
| LE (light efficiency) (lux/W)                 | 4933 |
| LE class (light efficiency class)             | A    |
| GFE (grease filtering efficiency)             | 7386 |
| GFE class (grease filtering efficiency class) | D    |
| Airflow in normal mode MIN (m3/h)             | 3045 |
| Airflow in normal mode MAX (m3/h)             | 499  |
| Acoustic power in normal mode MIN (dB)        | 435  |
| Acoustic power in normal mode MAX (dB)        | 676  |
| Po (energy consumption in off mode) (W)       | 0    |

### Integration directive EU 66/2014

|                                                            |     |
|------------------------------------------------------------|-----|
| f (time increase factor)                                   | 127 |
| EEl (Energy Efficiency Index)                              | 667 |
| QBEP (maximum efficiency at air flow point) (m3/h)         | 260 |
| PBEP (maximum efficiency at pressure point) (Pa)           | 270 |
| WBEP (power consumption at maximum efficiency) (W)         | 957 |
| WL (nominal power lighting system) (W)                     | 3   |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 148 |

### External Dimensions

|                           |     |
|---------------------------|-----|
| Width (mm)                | 600 |
| Depth (mm)                | 470 |
| Maximum total height (mm) | 776 |
| Minimum total height (mm) | 426 |
| Diamètre de sortie (mm)   | 150 |

### Characteristics

|                                       |                        |
|---------------------------------------|------------------------|
| Motor quantity                        | 1                      |
| Motor model                           | TT500                  |
| Maximum pressure (Pa)                 | 430                    |
| Filter technology                     | Aluminium mesh         |
| Control technology                    | Mechanical push button |
| Booster                               | -                      |
| Power levels                          | 3                      |
| Timer                                 | -                      |
| Filter saturation indicator           | -                      |
| Charcoal filter replacement indicator | -                      |
| Dimmer function                       | -                      |
| Connectivity                          | No                     |
| Remote control                        | -                      |
| Display                               | -                      |

### Lighting

|                |        |
|----------------|--------|
| Light model    | ECOLED |
| Ray technology | LED    |

### Installation

|                                         |          |
|-----------------------------------------|----------|
| Minimum distance to electric plate (mm) | 650      |
| Minimum distance to gas plate (mm)      | 650      |
| Recirculation option                    | √        |
| Charcoal filter                         | -        |
| Back draught shutter                    | Included |

|              |   |
|--------------|---|
| Inner shield | - |
|--------------|---|

**Electric connection**

|                           |         |
|---------------------------|---------|
| Nominal voltage (V)       | 220-240 |
| Nominal frequency (Hz)    | 50/60   |
| Nominal input power (W)   | 123     |
| Electric shock protection | Class I |
| Plug type                 | Type F  |

**Accessories**

|                           |          |
|---------------------------|----------|
| Activated charcoal filter | 02859492 |
| Noiseless flexible duct   | 02893002 |