




LEGEND 9010 X

Cod. **02029306**EAN **8422248110037**

GENERAL INFORMATION

EAN/UPC	8422248110037
Subfamily	Box

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	24,5
EEI class (energy efficiency class)	A+
FDE (fluid dynamic efficiency)	37
FDE class (fluid dynamic efficiency class)	A
LE (light efficiency) (lux/W)	17
LE class (light efficiency class)	C
GFE (grease filtering efficiency)	76,8
GFE class (grease filtering efficiency class)	C
Airflow in normal mode MIN (m3/h)	278,6
Airflow in normal mode MAX (m3/h)	550,9
Airflow in boost mode MIN (m3/h)	760,9
Acoustic power in normal mode MIN (dB)	52
Acoustic power in normal mode MAX (dB)	64
Acoustic power boost mode (dB)	70
Po (energy consumption in off mode) (W)	0,44
Ps (energy consumption in standby mode) (W)	0,44

Integration directive EU 66/2014

f (time increase factor)	0,7
EEI (Energy Efficiency Index)	39,6
QBEP (maximum efficiency at air flow point) (m3/h)	316,9
PBEP (maximum efficiency at pressure point) (Pa)	330
WBEP (power consumption at maximum efficiency) (W)	78,6
WL (nominal power lighting system) (W)	6
EMIDDLE (Average illuminance on the cooking surface) (lux)	103

External Dimensions

Width (mm)	700
Depth (mm)	495
Maximum total height (mm)	990
Minimum total height (mm)	745
Diamètre de sortie (mm)	150, 125

Characteristics

Motor quantity	1
Motor model	BT4DC
Filter technology	Aluminium mesh
Control technology	Electronic Soft Touch
Booster	√
Power levels	4
Filter saturation indicator	√
Charcoal filter replacement indicator	√
Dimmer function	√
Connectivity	√
Remote control	-
Display	Display_grafico

Lighting

Light model	SSLED BICOLOR
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	-
Charcoal filter	-

Back draught shutter	No
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	141
Electric shock protection	Class I
Power cord length (m)	0,7
Plug type	No plug

Accessories

Upper decorative duct extension	02861301
White decorative duct	-
Black decorative duct	-
Island tube booster	-
Back draught shutter	02832004
Activated charcoal filter	02859318
Noiseless flexible duct	02893002