




EAN 8422248375764



EAN/UPC	8422248375764
Subfamily	Integrated

AEC (Annual energy consumption) (kWh/year)	24,5
EEL class (energy efficiency class)	A
FDE (fluid dynamic efficiency)	26,4
FDE class (fluid dynamic efficiency class)	B
LE (light efficiency) (lux/W)	21,4
LE class (light efficiency class)	B
GFE (grease filtering efficiency)	64,8
GFE class (grease filtering efficiency class)	D
Airflow in normal mode MIN (m3/h)	21,6
Airflow in normal mode MAX (m3/h)	480,5
Acoustic power in normal mode MIN (dB)	53
Acoustic power in normal mode MAX (dB)	69,7
Po (energy consumption in off mode) (W)	0
Ps (energy consumption in standby mode) (W)	0

f (time increase factor)	1
EI (Energy Efficiency Index)	46,9
QBEP (maximum efficiency at air flow point) (m3/h)	281,1
PBEP (maximum efficiency at pressure point) (Pa)	227
WBEP (power consumption at maximum efficiency) (W)	67,1
WL (nominal power lighting system) (W)	6
EMIDDLE (Average illuminance on the cooking surface) (lux)	128,3

Width (mm)	445
Depth (mm)	270
Maximum total height (mm)	170
Minimum total height (mm)	170
Diamètre de sortie (mm)	150

Motor quantity	1
Motor model	K10 450 B
Maximum pressure (Pa)	294,3
Filter technology	Aluminium mesh
Control technology	Mechanical slider
Booster	-
Power levels	3
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	-
Remote control	-
Display	-

Light model	CSLED
Ray technology	LED

Minimum distance to electric plate (mm)	450
Minimum distance to gas plate (mm)	650
Recirculation option	-
Charcoal filter	√

Back draught shutter	-
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	116
Electric shock protection	Class II
Power cord length (m)	1
Plug type	No plug

Accessories

Upper decorative duct extension	No
White decorative duct	No
Black decorative duct	No
Island tube booster	No
Back draught shutter	02849003
MAX PRO Metal filter	No
Activated charcoal filter	02859489
Noiseless flexible duct	02893002
Recirculation kit	02800013