

**GENERAL INFORMATION**

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248003551 |
| Subfamily | Axial         |

**General features**

|                                        |                |
|----------------------------------------|----------------|
| Motor type                             | AC/SHADED POLE |
| Motor model                            | SP5812         |
| Motor power (W)                        | 15             |
| Lighting technology                    | N/A            |
| Light quantity                         | N/A            |
| Filter type                            | N/A            |
| Number of layers                       | N/A            |
| Control description                    | Potentiometer  |
| Power levels                           | N/A            |
| Timer                                  | √              |
| Hygro timer                            | -              |
| Electronic filter saturation indicator | -              |
| Dimmable lighting                      | -              |

**Installation**

|                           |           |
|---------------------------|-----------|
| Width (mm)                | 150       |
| Height (mm)               | 150       |
| Depth (mm)                | 87        |
| Total minimum height (mm) | 2300      |
| Outlet diameter (mm)      | 98        |
| Maximum pressure (Pa)     | 25        |
| Anti-return flap included | -         |
| Easy installation system  | Quick_Flx |

**Power connection**

|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 220-240  |
| Nominal frequency (Hz)    | 50/60    |
| Nominal input power (W)   | 15       |
| Electric shock protection | Class II |
| Plug type                 | No plug  |

**Accessories**

|                           |         |
|---------------------------|---------|
| Fixed grill               | 1910200 |
| Overpressure relief valve | 1910300 |
| Window fixing ring        | 1910100 |
| Backdraught seal          | 1990097 |

**Power and water connection**

|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 220-240  |
| Nominal frequency (Hz)    | 50/60    |
| Nominal input power (W)   | 15       |
| Electric shock protection | Class II |
| Plug type                 | No plug  |

# X-MART 10 MATIC T

Cod. 01016000

EAN 8422248003551

