




## E-100 GTH BK

Cod. **00900602**

EAN **8422248071895**



### GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248071895 |
| Subfamily | Axial         |

### General features

|  |                                |
|--|--------------------------------|
| Motor type                             | AC/SHADED POLE LOW CONSUMPTION |
| Motor model                            | SP5812                         |
| Motor power (W)                        | 8                              |
| Lighting technology                    | N/A                            |
| Light quantity                         | N/A                            |
| Filter type                            | N/A                            |
| Number of layers                       | N/A                            |
| Control description                    | Potentiometer                  |
| Power levels                           | 2                              |
| Timer                                  | √                              |
| Hygro timer                            | √                              |
| Electronic filter saturation indicator | -                              |
| Dimmable lighting                      | -                              |

### Installation

|                           |      |
|---------------------------|------|
| Width (mm)                | 150  |
| Height (mm)               | 150  |
| Depth (mm)                | 94   |
| Total minimum height (mm) | 2300 |
| Outlet diameter (mm)      | 98   |
| Maximum pressure (Pa)     | 20   |
| Anti-return flap included | -    |
| Easy installation system  | No   |

### Power connection

|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 220-240  |
| Nominal frequency (Hz)    | 50/60    |
| Nominal input power (W)   | 8        |
| Electric shock protection | Class II |
| Plug type                 | No plug  |

### Power and water connection

|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 220-240  |
| Nominal frequency (Hz)    | 50/60    |
| Nominal input power (W)   | 8        |
| Electric shock protection | Class II |
| Plug type                 | No plug  |