



## CG5-T600 X

Cod. 02005299

EAN 8422248097413



### GENERAL INFORMATION

EAN/UPC	8422248097413
Subfamily	Curved Glass

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	46
EEl class (energy efficiency class)	B
FDE (fluid dynamic efficiency)	204
FDE class (fluid dynamic efficiency class)	C
LE (light efficiency) (lux/W)	4933
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	7386
GFE class (grease filtering efficiency class)	D
Airflow in normal mode MIN (m3/h)	3045
Airflow in normal mode MAX (m3/h)	499
Acoustic power in normal mode MIN (dB)	435
Acoustic power in normal mode MAX (dB)	676
Po (energy consumption in off mode) (W)	0

### Integration directive EU 66/2014

f (time increase factor)	127
EEl (Energy Efficiency Index)	667
QBEP (maximum efficiency at air flow point) (m3/h)	260
PBEP (maximum efficiency at pressure point) (Pa)	270
WBEP (power consumption at maximum efficiency) (W)	957
WL (nominal power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	148

### External Dimensions

Width (mm)	600
Depth (mm)	470
Maximum total height (mm)	776
Minimum total height (mm)	426
Diamètre de sortie (mm)	150

### Characteristics

Motor quantity	1
Motor model	TT500
Maximum pressure (Pa)	430
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	-
Power levels	3
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	No
Remote control	-
Display	-

### Lighting

Light model	ECOLED
Ray technology	LED

### Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	√
Charcoal filter	-
Back draught shutter	Included

Inner shield -

---

**Electric connection**

---

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50/60
Nominal input power (W)	123
Electric shock protection	Class I
Plug type	Type F

---

**Accessories**

---

Activated charcoal filter	02859492
Noiseless flexible duct	02893002

---