




LENA 900 GWH

Cod. **02059011**

EAN **8422248346559**



GENERAL INFORMATION

| | |
|-----------|---------------|
| EAN/UPC | 8422248346559 |
| Subfamily | Angle Glass |

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

| | |
|---|------|
| AEC (Annual energy consumption) (kWh/year) | 48,3 |
| EEI class (energy efficiency class) | B |
| FDE (fluid dynamic efficiency) | 19,6 |
| FDE class (fluid dynamic efficiency class) | C |
| LE (light efficiency) (Lux/W) | 21 |
| LE class (light efficiency class) | B |
| GFE (grease filtering efficiency) | 66,3 |
| GFE class (grease filtering efficiency class) | D |
| Airflow in normal mode MIN (m3/h) | 2851 |
| Airflow in normal mode MAX (m3/h) | 4548 |
| Acoustic power in normal mode MIN (dB) | 48 |
| Acoustic power in normal mode MAX (dB) | 58 |
| Po (energy consumption in off mode) (W) | 0,48 |

Integration directive EU 66/2014

| | |
|--|-------|
| f (time increase factor) | 1,3 |
| EEI (Energy Efficiency Index) | 68,9 |
| QBEP (maximum efficiency at air flow point) (m3/h) | 245,1 |
| PBEP (maximum efficiency at pressure point) (Pa) | 276 |
| WBEP (power consumption at maximum efficiency) (W) | 95,7 |
| WL (nominal power lighting system) (W) | 3,9 |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 81 |

Characteristics

| | |
|---------------------------------------|--------------------------|
| Motor quantity | 1 |
| Filter technology | Aluminium mesh |
| Control technology | Electronic Touch Control |
| Power levels | 3 |
| Timer | √ |
| Filter saturation indicator | - |
| Charcoal filter replacement indicator | - |
| Dimmer function | √ |
| Connectivity | No |
| Remote control | - |
| Display | Display |

Lighting

| | |
|----------------|--------|
| Light model | ECOLED |
| Ray technology | LED |

Electric connection

| | |
|---------------------------|---------|
| Nominal voltage (V) | 220-240 |
| Nominal frequency (Hz) | 60 |
| Nominal input power (W) | 120 |
| Electric shock protection | Class I |
| Plug type | Type F |

Accessories

| | |
|---------------------------|--|
| Back draught shutter | B30-TG18-015-JB (2pcs included) |
| Activated charcoal filter | Big Round carbon filter B15-TF08-097-JB (optional) |

