



# X-MART 12 MATIC T

Cod. 01026000

EAN 8422248003582



## GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248003582 |
| Subfamily | Axial         |

## General features

|                                        |                |
|----------------------------------------|----------------|
| Motor type                             | AC/SHADED POLE |
| Motor model                            | SP5820         |
| Motor power (W)                        | 20             |
| Lighting technology                    | N/A            |
| Light quantity                         | N/A            |
| Filter type                            | N/A            |
| Number of layers                       | N/A            |
| Control description                    | N/A            |
| Power levels                           | 1              |
| Timer                                  | √              |
| Hygro timer                            | -              |
| Electronic filter saturation indicator | -              |
| Dimmable lighting                      | -              |

## Installation

|                           |           |
|---------------------------|-----------|
| Width (mm)                | 170       |
| Height (mm)               | 170       |
| Depth (mm)                | 139       |
| Total minimum height (mm) | 170       |
| Outlet diameter (mm)      | 118       |
| Anti-return flap included | √         |
| Easy installation system  | Quick-Fix |

## Power connection


|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 230      |
| Nominal input power (W)   | 20       |
| Electric shock protection | Class II |

## Accessories

|                  |                          |
|------------------|--------------------------|
| Fixed grill      | QUICK FIX GRIP           |
| Backdraught seal | AUTOMATIC SHUTTER SYSTEM |

## Power and water connection

|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 230      |
| Nominal input power (W)   | 20       |
| Electric shock protection | Class II |



|                 | Ø A | B   | C   | D      |
|-----------------|-----|-----|-----|--------|
| X-MART 10 MATIC | 98  | 150 | 87  | 38 máx |
| X-MART 12 MATIC | 118 | 170 | 101 | 38 máx |
| X-MART 15 MATIC | 148 | 194 | 120 | 38 máx |