




ISB 603 BK

ISB 603 BK

 Cod. **08073212** EAN **8422248112703**

- 3 cooking areas:**
 - Right: 1 area **with Booster function** of ø280mm of 2.3kW (max. 3kW)
 - Front Left: 1 area **with Booster function** of ø210mm of 2.3kW (max. 2.6kW)
 - Rear Left: 1 area **with Booster function** of ø160mm of 1.2kW (max. 1.5kW)
- Slider Touch Control** with acoustic warning
- 9 adjustable power levels + Booster
- Timer function for each area
- Countdown alarm
- Automatic pan detection
- Safety lock
- Residual heat indicator
- Automatic safety switch-off
- 59 cm wide**
- Total power 7.1kW**



Code	08073212
EAN	8422248112703
Model	ISB 603 BK
Type	Induction
Product fiche	
Cooking zones	3
Right front zone: Diameter (mm)	-
Right front zone: Power (kW)	-
Right front zone: Booster (kW)	-
Right front zone: Consumption (Wh/kg)	-
Right rear zone: Diameter (mm)	280
Right rear zone: Power (kW)	2,3
Right rear zone: Booster (kW)	3
Right rear zone: Consumption (Wh/kg)	180,8
Central front zone: Diameter (mm)	-
Central front zone: Power (kW)	-
Central front zone: Booster (kW)	-
Central front zone: Consumption (Wh/kg)	-
Central rear zone: Diameter (mm)	-
Central rear zone: Power (kW)	-
Central rear zone: Booster (kW)	-
Central rear zone: Consumption (Wh/kg)	-
Front left zone: Diameter (mm)	210
Front left zone: Power (kW)	2,3
Front left zone: Booster (kW)	2,6
Front left zone: Consumption (Wh/kg)	184,1
Left rear zone: Diameter (mm)	160
Left rear zone: Power (kW)	1,2
Left rear zone: Booster (kW)	1,5
Left rear zone: Consumption (Wh/kg)	181,7
Energy consumption of the hob (Wh/kg)	182,2
Dimensions	
Product width (mm)	590
Product depth (mm)	520
Product height (mm)	58
Built-in height (mm)	565
Built-in depth (mm)	495
Ventilation slot (mm)	5
Fixing system	Quick-Fix System
Finishing	
Colour	Negro
Aesthetic	Rounded
Control	
Control type	Slider
Power selection (+/-)	Centralized
Power levels	9 + Booster
Timer	Yes
Countdown alarm	Yes
Power management	No
Security	
Safety lock	Yes
Residual heat indicator	Yes
Automatic pan detection	Yes
Automatic safety switch-off	Yes
Protection against liquid spillage	Yes
Electrical connection	
Nominal voltage (V)	220-240
Mains frequency (Hz)	50-60
Max Product power (kW)	7,1