




LHV 190

Cod. 00661000

EAN 8422248009331



INFORMACIÓN GENERAL

| | |
|-----------|---------------|
| EAN/UPC | 8422248009331 |
| Subfamily | Wall |

General features

| | |
|--|--------------|
| Motor type | AC/INDUCTION |
| Motor power (W) | 30 |
| Lightning Technology | N/A |
| Light Quantity | N/A |
| Filter Type | N/A |
| Number of layers | N/A |
| Control description | N/A |
| Power levels | N/A |
| Timer | - |
| Timer Hygro | - |
| Electronic filter saturation indicator | - |
| Dimmable lighting | - |

Installation

| | |
|---------------------------|------|
| Width (mm) | 250 |
| Height (mm) | 250 |
| Depth (mm) | 97 |
| Total minimum height (mm) | 2300 |
| Outlet diameter (mm) | 194 |
| Maximum pressure (Pa) | 25 |
| Anti-return flap included | - |
| Easy installation system | No |

Power connection

| | |
|-----------------------------------|---------|
| Rated voltage (V) | 230 |
| Rated frequency (Hz) | 50 |
| Rated power input (W) | 30 |
| Protection against electric shock | Class I |
| Plug type | No plug |

Accessories

| | |
|----------------------|---------|
| Overpressure shutter | 1560190 |
|----------------------|---------|

Power and water connection

| | |
|-----------------------------------|---------|
| Rated voltage (V) | 230 |
| Rated frequency (Hz) | 50 |
| Rated power input (W) | 30 |
| Protection against electric shock | Class I |
| Plug type | No plug |