DECORATIVAS **CRISTAL**



CG5-T600 X

Cod. **02005299** EAN **8422248097413**

INFORMACIÓN GENERAL

EAN/UPC	8422248097413
Subfamily	Curved Glass

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Energy consumption per year) (kWh/año)	46
EEI class (Energy efficiency class)	B
FDE (Fluid dynamic efficiency)	204
FDE class (Fluid dynamic efficiency class)	C
LE (Light efficiency) (lux/W)	4933
LE class (Light efficiency class)	A
GFE (Grease filtering efficiency)	7386
GFE Class (Grease filtering efficiency class)	D
Normal mode airflow MIN (m3/h)	3045
Normal mode airflow MAX (m3/h)	499
Normal mode acustic power MIN (dB)	435
Normal mode acustic power MAX (dB)	676
Po (Off-mode power consumption) (W)	0

Integration directive EU 66/2014

f (Factor Increase in the time)	127
EEI (Energy efficiency Index)	667
QBEP (Maximum airflow point efficiency) (m3/h)	260
PBEP (Maximum pressure point efficiency) (Pa)	270
WBEP (Electrical power consumption at maximum efficiency) (W)	957
WL (Rated power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	148

External Dimensions

Width (mm)	600
Depth (mm)	470
Maximum Total Height (mm)	776
Minimum Total Height (mm)	426
Outlet Diameter (mm)	150

Characteristics

Motor Quantity	1
Motor Model	TT500
Maximum Pressure (Pa)	430
Filter Technology	Aluminium mesh
Control Tecnology	Mechanical push button
Booster	-
Power levels	3
Timer	-
Filter Saturation Indicator	-
Charcoal Filter Change Indicator	-
Dimmer Function	-
Connectivity	No
Remote control	-
Display	-

Lighting

Light Model	ECOLED
Lightning Technology	LED

Installation

Minimum distance to an electric cooktop (mm)	650
Minimum distance to a gas cooktop (mm)	650
Recirculation Option	√
Charcoal Filter	-

Back Draught Shutter	Included
Inner shield	-

Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50/60
Rated power input (W)	123
Protection against electric shock	Class I
Plug type	Type F

Accessories

Active Charcoal Filter	02859492
Noiseless Flexible Duct	02893002