



CG5-T900 X

Cod. **02008299**

EAN **8422248108102**



INFORMACIÓN GENERAL

EAN/UPC	8422248108102
Subfamily	Curved Glass

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Energy consumption per year) (kWh/año)	48
EEl class (Energy efficiency class)	B
FDE (Fluid dynamic efficiency)	222
FDE class (Fluid dynamic efficiency class)	C
LE (Light efficiency) (lux/W)	4933
LE class (Light efficiency class)	A
GFE (Grease filtering efficiency)	8287
GFE Class (Grease filtering efficiency class)	C
Normal mode airflow MIN (m3/h)	296
Normal mode airflow MAX (m3/h)	495
Normal mode acoustic power MIN (dB)	455
Normal mode acoustic power MAX (dB)	66
Po (Off-mode power consumption) (W)	0

Integration directive EU 66/2014

f (Factor Increase in the time)	12
EEl (Energy efficiency Index)	644
QBEP (Maximum airflow point efficiency) (m3/h)	2875
PBEP (Maximum pressure point efficiency) (Pa)	288
WBEP (Electrical power consumption at maximum efficiency) (W)	1036
WL (Rated power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	148

External Dimensions

Width (mm)	900
Depth (mm)	470
Maximum Total Height (mm)	776
Minimum Total Height (mm)	426
Outlet Diameter (mm)	150

Characteristics

Motor Quantity	1
Motor Model	TT500
Maximum Pressure (Pa)	435
Filter Technology	Aluminium mesh
Control Technology	Mechanical push button
Booster	-
Power levels	3
Timer	-
Filter Saturation Indicator	-
Charcoal Filter Change Indicator	-
Dimmer Function	-
Connectivity	No
Remote control	-
Display	-

Lighting

Light Model	ECOLED
Lightning Technology	LED

Installation

Minimum distance to an electric cooktop (mm)	650
Minimum distance to a gas cooktop (mm)	650
Recirculation Option	√
Charcoal Filter	-

Back Draught Shutter	Included
Inner shield	-

Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50/60
Rated power input (W)	123
Protection against electric shock	Class I
Plug type	Type F

Accessories

Active Charcoal Filter	02859492
Noiseless Flexible Duct	02893002