EXTRACCIÓN **AXIAL**




# B-12 MATIC TIMER

Cod. **00926000** EAN **8422248110808**

## INFORMACIÓN GENERAL

| | |
|---|---|
| EAN/UPC | 8422248110808 |
| Subfamily | Axial |

### General features

| | |
|---|---|
| Motor type | AC/SHADED POLE |
| Motor Model | SP5820 |
| Motor power (W) | 20 |
| Lightning Technology | N/A |
| Light Quantity | N/A |
| Filter Type | N/A |
| Number of layers | N/A |
| Control description | N/A |
| Power levels | 1 |
| Timer | √ |
| Timer Hygro | - |
| Electronic filter saturation indicator | - |
| Dimmable lighting | - |

### Installation

| | |
|---|---|
| Width (mm) | 180 |
| Height (mm) | 180 |
| Depth (mm) | 101 |
| Total minimum height (mm) | 180 |
| Outlet diameter (mm) | 118 |
| Anti-return flap included | √ |

### Power connection

| | |
|---|---|
| Rated voltage (V) | 230 |
| Rated frequency (Hz) | 50/60 |
| Rated power input (W) | 20 |
| Protection against electric shock | Class II |
| Plug type | No plug |

### Accessories

| | |
|---|---|
| Backdraugth Shutter | With automatic shutter. |

### Power and water connection

| | |
|---|---|
| Rated voltage (V) | 230 |
| Rated frequency (Hz) | 50/60 |
| Rated power input (W) | 20 |
| Protection against electric shock | Class II |
| Plug type | No plug |

