



# X-MART 12 MATIC T

Cod. 01026000

EAN 8422248003582



## INFORMACIÓN GENERAL

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248003582 |
| Subfamily | Axial         |

### General features

|                                        |                |
|----------------------------------------|----------------|
| Motor type                             | AC/SHADED POLE |
| Motor Model                            | SP5820         |
| Motor power (W)                        | 20             |
| Lightning Technology                   | N/A            |
| Light Quantity                         | N/A            |
| Filter Type                            | N/A            |
| Number of layers                       | N/A            |
| Control description                    | N/A            |
| Power levels                           | 1              |
| Timer                                  | √              |
| Timer Hygro                            | -              |
| Electronic filter saturation indicator | -              |
| Dimmable lighting                      | -              |

### Installation

|                           |           |
|---------------------------|-----------|
| Width (mm)                | 170       |
| Height (mm)               | 170       |
| Depth (mm)                | 139       |
| Total minimum height (mm) | 170       |
| Outlet diameter (mm)      | 118       |
| Anti-return flap included | √         |
| Easy installation system  | Quick-Fix |

### Power connection


|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 230      |
| Rated power input (W)             | 20       |
| Protection against electric shock | Class II |

### Accessories

|                     |                          |
|---------------------|--------------------------|
| Fixed Grid          | QUICK FIX GRIP           |
| Backdraught Shutter | AUTOMATIC SHUTTER SYSTEM |

### Power and water connection

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 230      |
| Rated power input (W)             | 20       |
| Protection against electric shock | Class II |



|                 | Ø A | B   | C   | D      |
|-----------------|-----|-----|-----|--------|
| X-MART 10 MATIC | 98  | 150 | 87  | 38 máx |
| X-MART 12 MATIC | 118 | 170 | 101 | 38 máx |
| X-MART 15 MATIC | 148 | 194 | 120 | 38 máx |