



## X-MART 15 MATIC INOX

Cod. **01065000**EAN **8422248003780**

|                 | Ø A | B   | C   | D      |
|-----------------|-----|-----|-----|--------|
| X-MART 10 MATIC | 98  | 150 | 87  | 38 máx |
| X-MART 12 MATIC | 118 | 170 | 101 | 38 máx |
| X-MART 15 MATIC | 148 | 194 | 120 | 38 máx |

### INFORMACIÓN GENERAL

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248003780 |
| Subfamily | Axial         |

### General features

|                      |                |
|----------------------|----------------|
| Motor type           | AC/SHADED POLE |
| Motor Model          | SP5820         |
| Motor power (W)      | 25             |
| Lightning Technology | LED            |
| Light Quantity       | 1              |
| Filter Type          | N/A            |
| Number of layers     | N/A            |
| Control description  | N/A            |
| Power levels         | 1              |
| Timer                | -              |
| Timer Hygro          | -              |
| Dimmable lighting    | -              |

### Installation

|                           |           |
|---------------------------|-----------|
| Width (mm)                | 194       |
| Height (mm)               | 194       |
| Depth (mm)                | 158       |
| Total minimum height (mm) | 194       |
| Outlet diameter (mm)      | 148       |
| Easy installation system  | Quick-Fix |

### Power connection

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 220-240  |
| Rated frequency (Hz)              | 50/60    |
| Rated power input (W)             | 25       |
| Protection against electric shock | Class II |
| Plug type                         | No plug  |

### Accessories

|                     |                          |
|---------------------|--------------------------|
| Fixed Grid          | QUICK FIX GRIP           |
| Backdraught Shutter | Automatic shutter system |

### Power and water connection

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 220-240  |
| Rated frequency (Hz)              | 50/60    |
| Rated power input (W)             | 25       |
| Protection against electric shock | Class II |
| Plug type                         | No plug  |