




X-MART 12 MATIC INOX T

Cod. **01056000**

EAN **8422248003766**



| | Ø A | B | C | D |
|-----------------|-----|-----|-----|--------|
| X-MART 10 MATIC | 98 | 150 | 87 | 38 máx |
| X-MART 12 MATIC | 118 | 170 | 101 | 38 máx |
| X-MART 15 MATIC | 148 | 194 | 120 | 38 máx |

INFORMACIÓN GENERAL

| | |
|-----------|---------------|
| EAN/UPC | 8422248003766 |
| Subfamily | Axial |

General features

| | |
|--|----------------|
| Motor type | AC/SHADED POLE |
| Motor Model | SP5820 |
| Motor power (W) | 20 |
| Lightning Technology | LED |
| Light Quantity | 1 |
| Filter Type | N/A |
| Number of layers | N/A |
| Control description | N/A |
| Power levels | 1 |
| Timer | √ |
| Timer Hygro | - |
| Electronic filter saturation indicator | - |
| Dimmable lighting | - |

Installation

| | |
|---------------------------|-----------|
| Width (mm) | 170 |
| Height (mm) | 170 |
| Depth (mm) | 149 |
| Total minimum height (mm) | 170 |
| Outlet diameter (mm) | 118 |
| Anti-return flap included | √ |
| Easy installation system | Quick-Fix |

Power connection

| | |
|-----------------------------------|----------|
| Rated voltage (V) | 220-240 |
| Rated frequency (Hz) | 50/60 |
| Rated power input (W) | 20 |
| Protection against electric shock | Class II |
| Plug type | No plug |

Accessories

| | |
|---------------------|---------------------------|
| Fixed Grid | QUICK FIX GRIP, |
| Backdraught Shutter | Automatic shutter system. |

Power and water connection

| | |
|-----------------------------------|----------|
| Rated voltage (V) | 220-240 |
| Rated frequency (Hz) | 50/60 |
| Rated power input (W) | 20 |
| Protection against electric shock | Class II |
| Plug type | No plug |